

# GXP – 750 PerfecTear Plus™

## Technical Data

**Product Description** – A medium tack lay-flat paper application tape for vinyl graphics used in sign making, screen printing and surface protection. The product consists of a self-wound, standard grade saturated backing coated with a specially formulated latex pressure sensitive adhesive.

### Product Characteristics

<b>Construction</b>	
Backing	White translucent latex saturated paper
Adhesive	Water based natural latex
Total Thickness	4 mil (nominal)
<b>Performance</b>	
Tensile Strength (psi)	
MD	20
Elongation (%)	2.4
Adhesion (oz/in)	
PSTC#4 bright annealed ss	8.0 - 14.0

The physical properties listed above are typical values and are not to be considered as specifications. Our suggestions for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for their internal use. Main Tape assumes no liability for claims beyond those outlined within our Limited Warranty, which includes replacement value of Main Tape product proven defective. For full disclosure of the Limited Warranty, please contact your Main Tape representative.

**Typical Uses** - Excellent for small and medium-sized computer-cut letters, in which adhesion to exposed liner is required. Laminates smoothly to UV inks and clear coated 4 color process graphics. Offers superior conformability to silicone release liners. Resists wrinkling, tunneling and edge curling.